Javelin DNA Series



High speed desktop card printers with added new features

The Javelin desktop series now has 3 main models: the **Javelin DNA**, which is an entry-level manual feed printer, the **Javelin DNA PRO** which has input and output hoppers (auto feed) and the **Javelin MBOSS** with a unique printhead for pre-embossed financial cards. **New features on all models include** a mobile app, enabling you to send card images from your Android or tablet, a rewrite feature for re-usable cards and Data Shield to protect the data visible on the ribbon when printer to a card and software security lock.



Javelin DNA Series



Printer specifications

Specifications

Print technology Dye-sublimation, direct-to-card

Print resolution

300 dpi

Print area

53.98 x 85.6mm / 3.370" x 2.125" (CR-80 cards)

Print speed

• 180-200 cph (YMCKO single-side)

- 100 cph (YMCKOK dual-sided) • 800 cph (monochrome printing)
- Print mode Manual, automatic single or dual-sided (optional)

Printer memory RAM: 128 Mb, CPU: 32 bit processor

Communications interface

USB 2.0

Easy to use, plug and print operation

- · LCD display with graphical notifications • 4 x LED status indicators
- · Drop in ribbon cassette with easy handling · Automatic ribbon identification and setting
- · Easy maintenance access

Printer security

Support for Kensington® security lock

Printer dimensions (HxWxD)

Javelin DNA/PRO/MBOSS: 305x184x228mm / 10.6"x7.9"x15.9"

Weight

· Javelin DNA: 3.7kg, 8.16lb Javelin DNA PRO/MBOSS: 4.5kg, 9.92lbs

- **Power supply** • Input: 220-240V/110-115V, 50-60 Hz
- Output: DC 24V, 2.5A
- FCC Class A, CE and CCC, KCC, Energy Star app

Operating environment

- Temperature: 5°C to 40°C, 41°F to 104°F
- Humidity: 20% 90% (non-condensing)

Storage conditions

- Temperature: -10°C to 60°C, 14°F to 140°F · Humidity: 20% to 90% (non-condensing)
- Sound (ISO 7779)

Sound pressure less than 48dB (A)

Certifications

RoHs, CE, FCC, CQC, UL, WEEE, Proposition 65 (California, USA)

Warranty

30 months

Card specifications

Input hopper capacity 100 cards (0.76 mm / 30 mil thickness)

Output hopper capacity

60 cards (front)

Card thickness

• 0.25 mm - 1.25 mm / 10 mil - 50 mil Gauge adjustment

Card types CR-80 PVC, PVC-C, rewrite (optional)

Software specification

Printer driver

Windows® 7, 8.1, 10, Vista, XP

Integration tools

• EDIsecure® middleware · SDK available for system integrators

Code 39, Code 128 B&C with and without check digit. 2 of 5 interleaved UPC-A, EAN 8 & EAN 13 PDF-417 2D barcode and other symbols can be printed via Windows drivers

Options

Magnetic stripe encoding

ISO 7811 HiCo/LoCo (factory fit only)

Smart card / Contactless encoding

- · Contact PC/SC, EMV compliant
- Smart contact station: ISO 7816-2
- ISO14443A, B, ISO15693, MIFARE[®], DESFire[®] HID iClass®

Printer security

- Mechanical locks
- Electromagnetic locks

Communications interface WiFi 802.11 a/b/g

WiFi to mobile

Link to mobile app.

Lamination Inline Javelin laminator

Consumables

To ensure print quality and card durability, printhead lifespan and overall printer reliability, use Javelin ribbons only.


Supply cores and cassettes are recyclable. Packaging is recycled.

Ribbon program	Part No.
• Colour YMCKO (up to 200 prints)	61123501
Colour YMCKOK (up to 167 prints)	61123511
• Colour (half panel YMC)KO (up to 400 prints)	61123513
• KO - Black /Overlay (up to 500 prints)	61123201
• Monochrome K - Black (up to 1000 prints)	61123110
• Mono White (up to 1000 prints)	61123113
• Mono Red (up to 1000 prints)	61123114
• Mono Blue (up to 1000 prints)	61123112
• Mono: Silver (up to 1000 prints)	61123117
• Mono: Gold (up to 1000 prints)	61123116
• Scratch-off (up to 1000 prints)	61123118
• Cleaning kit - 5x cleaning cards	61100929

- 5x 6" swabs
- 1x long cleaning T-card



JavelinDNAseries A4 V1



javelin-global.com Email: sales@javelin-global.com



Visit us to find out more

Secure issuance solutions, it's in our DNA





 Hopper locks Kensington lock