



Javelin Laminator

High performance inline / stand-alone card laminator



The **Javelin laminator** maximizes the lifetime use and durability of a card up to 5 to 10 years as well as protecting your card information from being counterfeited, duplicated, and tampered with.

It provides simultaneous dual-sided laminating at faster speeds and with shorter warm up times.






The Javelin Laminator is so versatile it can be used as a standalone product or fits perfectly inline with any of the Javelin DNA series printers.

Laminator delivers...

- ▶ Simultaneous dual-sided laminating
- ▶ 20s per card (single or dual-sided)
- ▶ Standard or customized holographic or clear laminate
- ▶ Continuous overlay film or patch laminate

Ideal for...

- ▶ National ID cards
- ▶ Driving licenses
- ▶ Resident cards
- ▶ Corporate cards
- ▶ Campus/student cards



Tel: 0800 505 3828



javelin-global.com
Email: sales@javelin-global.com



Javelin Global Ltd
B1 Moorfield Point, Slyfield Industrial Park, Guildford, Surrey, GU1 1RU, UK

Secure issuance solutions, it's in our DNA

JAVELIN
GLOBAL



Javelin Laminator

Laminator specifications

Specifications

Technology

Single and dual-sided simultaneous lamination

Lamination speed

20s per card (single or dual-sided)

Laminating temperature

120°C to 195°C

Warm-up time

40 seconds @ 120°C

Display

LCD and LED display with graphical notifications

Communications interface

USB 2.0, RS232C

Laminator security

Support for Kensington® security lock

Dimensions (HxWxD)

323 x 214 x 314mm

Weight

9.6kg

Power supply

- Input: 100-240V/110-115V, 50-60 Hz
- Output: DC 24V, 2.5A
- Single or dual : 600W (DC 24V, AC 220V)

Operating environment

- Temperature: 15°C to 30°C
- Humidity: 20% - 60% (non-condensing)

Storage conditions

- Temperature: -5°C to 70°C
- Humidity: 20% to 70% (non-condensing)

Certifications

RoHs, CE, FCC, CQC, UL, WEEE, VCCI, KCC

Warranty

2 years

Card specifications

Input hopper capacity (optional)

100 cards

Output hopper capacity

150 cards

Card thickness

0.76 mm - 1.0 mm / 30 mil - 40 mil

Lamination area

53.98 x 85.6mm / 3.370" x 2.125" (CR-80 cards)

Card types

CR-80 PVC, PVC-C

Software specification

Printer driver

Windows® 7, 8.1, 10, Vista, XP, Server 2003/2008

Options

Card hopper

Auto card feeding 100 card hopper

Output stacker

150 card capacity

Security

Enclosure lock

Add ons

Inline connection kit (bracket and plinth)



Consumables

To ensure print quality and card durability, printhead lifespan and overall printer reliability, use Javelin lamination film only.

Supply cores and cassettes are recyclable. Packaging is recycled.

Lamination program

	Part No.
• Clear 1 mil patch	61122101
• Holo 1 mil patch	61122103
• Clear Varnish Overlay	61122111
• Holo Varnish Overlay	61122113

Coming soon

- Clear 1mil Patch with smart cut-out
(xxxx prints)
- Clear 0.5mil Patch with smart cut-out
(xxxx prints)

JavelinLaminator A4 V1



Tel: 0800 505 3828



javelin-global.com

Email: sales@javelin-global.com



Javelin Global Ltd

B1 Moorfield Point, Slyfield Industrial Park, Guildford, Surrey, GU1 1RU, UK



Visit us

to find out more

Secure issuance solutions, it's in our DNA

JAVELIN
GLOBAL